

PRODUCT DATASHEET

A BULB 10W LOOX



Areas of application

- Home
- Hotels and Catering centers
- Supermarkets and malls
- Office and Residential Buildings
- Factory, plant, warehouse

Product benefits

- Energy savings with high system efficacy: up to 110 lm/W
- High quality aluminum housing
- Luminaire designed for easy maintenance
- Professional optics with wide beam angle of 200°
- Low maintenance and operation costs due to long lifetime of LED
- Good color consistency
- Good color rendering

Product features

- Power factor: > 0.5
- Type of protection: IP20
- Lifetime(L70): up to 25,000 Hrs
- Color rendering index R_a : > 80




TECHNICAL DATA

Electrical data

| | |
|------------------------|-----------|
| Nominal wattage | 10 W |
| Nominal voltage | 220-240 V |
| Power factor λ | 0.5 |


Photometrical data

| | |
|--------------------------|-----------------|
| Luminous flux | 1000 lm |
| Luminous efficacy | 110 lm/W |
| Color temperature | 2700 K - 6500 K |
| Color rendering index Ra | 80 |



Dimensions & Weight

| | |
|----------------|----------|
| Product weight | 39g |
| Base | B22 |
| Dimension | 110*60mm |



Materials & Colors

| | |
|---------------|-------|
| Product color | White |
| Housing color | White |
| Body material | PP |

Application & Mounting

| | |
|---------------------------|--------------|
| Ambient temperature range | -30...+50 °C |
| Type of protection | IP20 |

| | |
|-------------------------|---------|
| Dimmable | No |
| Mounting location | Pendant |
| Application environment | Indoor |

Lifespan

| | |
|----------|-----------|
| Lifespan | 25000 hrs |
| Waranty | 3years |

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.