





### Areas of application

- Home
- Hotels and Catering centers
- Supermarkets and malls
- Office and Residential Buildings

#### Product benefits

- Energy savings with high system efficacy: up to 90 lm/W
- High quality aluminum housing
- Luminaire designed for easy maintenance
- Professional optics with wide beam angle of 120°
- Low maintenance and operation costs due to long lifetime of LED
- Good color consistency
- Good color rendering

#### **Product features**

- Power factor: > 0.5

- Type of protection: IP20

- Lifetime(L70): up to 25,000 Hrs

- Color rendering index Ra: > 80




### TECHNICAL DATA

### Electrical data

Nominal wattage	15W
Nominal voltage	85-265 V
Power factor λ	0.5

### Photometrical data

Luminous flux	1300 lm
Luminous efficacy	90 lm/W
Color temperature	2700 K-4000K-6500 K
Color rendering index Ra	80



## Cut size & Weight

Product weight	300g
Cut size	105mm

#### Materials & Colors

Product color	White
Housing color	White
Body material	PP

### **Application & Mounting**

Ambient temperature range	-30+50 °C
Type of protection	IP20

Dimmable	No
Mounting location	Pendant
Application environment	Indoor

# Lifespan

Lifespan	25000 hrs
waranty	5years

## DISCLAIMER

 $\label{thm:continuous} \textbf{Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.}$