





Areas of application

- Home
- Hotels and Catering centers
- Supermarkets, shops and malls
- Office and Residential Buildings

Product benefits

- Energy savings with high system efficacy: up to 100 lm/W
- High quality aluminum housing
- Luminaire designed for easy maintenance
- Professional optics with different beam angle of 24º/36º
- Low maintenance and operation costs due to long lifetime of LED
- Good color consistency
- Good color rendering

Product features

- Osram chip
- With Anti-glare property
- Power factor: > 0.5
- Type of protection: IP40
- Lifetime(L70): up to 50,000 Hrs
- Color rendering index R_a: > 90




TECHNICAL DATA

Electrical data

Nominal wattage	25 W
Nominal voltage	220-240 V
Power factor λ	0.5

Photometrical data

Luminous flux	2500 lm
Luminous efficacy	100 lm/W
Color temperature	2700K-4000K-6500K
Color rendering index Ra	90



Dimension & Weight

Dimension	160*H83mm
Cut size	135mm
weight	324.3g

Materials & Colors

Product color	White-Black
Body material	Die cast Aluminium

Application & Mounting

Ambient temperature range	-30+50 °C
Type of protection	IP40

Dimmable	No
Mounting location	Pendant
Application environment	Indoor

Lifespan

Lifespan	50000 hrs
waranty	5years

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.