





#### Areas of application

- Home
- Hotels and Catering centers
- Supermarkets, shops and malls
- Office and Residential Buildings

#### Product benefits

- Energy savings with high system efficacy: up to 75 lm/W
- High quality aluminum housing
- Luminaire designed for easy maintenance
- Professional optics with wide beam angle 30°
- Low maintenance and operation costs due to long lifetime of LED
- Good color consistency
- Good color rendering

#### **Product features**

- Power factor: > 0.5

- Type of protection: IP20

Lifetime(L70): up to 25,000 Hrs

- Color rendering index Ra: >70




#### TECHNICAL DATA

## Electrical data

Nominal wattage	12w
Nominal voltage	110-265 V
Power factor $\lambda$	0.5

#### Photometrical data

Luminous flux	900 lm
Luminous efficacy	75 lm/W
Color temperature	2700K -6500K
Color rendering index Ra	70



#### Dimension

Dimension	75*100 mm
weight	350g

## Materials & Colors

Product color	White-Black
Body material	Die cast Aluminium

# Application & Mounting

Ambient temperature range	-30+50 °C
Type of protection	IP20

Dimmable	No
Mounting location	Pendant
Application environment	Indoor

# Lifespan

Lifespan	25000 hrs
waranty	2years

# DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.