





#### Areas of application

- Home
- Hotels and Catering centers
- Supermarkets and malls
- Office and Residential Buildings
- Factory, plant, warehouse

#### Product benefits

- Energy savings with high system efficacy: up to 78 lm/W
- High quality aluminum housing
- Luminaire designed for easy maintenance
- Professional optics with wide beam angle of 110°
- Low maintenance and operation costs due to long lifetime of LED
- Good color consistency
- Good color rendering

#### **Product features**

- Power factor: > 0.7

- Type of protection: IP20

- Lifetime(L70): up to 25,000 Hrs

- Color rendering index R<sub>a</sub>: > 80




## TECHNICAL DATA

## Electrical data

Nominal wattage	7W
Nominal voltage	170-265 V
Power factor $\lambda$	0.7

### Photometrical data

Luminous flux	530 lm
Luminous efficacy	78 lm/W
Color temperature	2700 K-6500 K
Color rendering index Ra	80



# Dimensions & Weight

Product weight	32g
Base	Mr16
Dimension	53*50mm

### Materials & Colors

Product color	White
Housing color	White
Body material	PP

# Application & Mounting

Ambient temperature range	-30+50 °C
Type of protection	IP20

Dimmable	No
Mounting location	Pendant
Application environment	Indoor

# Lifespan

Lifespan	25000 hrs
waranty	3years

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.