

PRODUCT DATASHEET

RECESSED LINEAR LIGHT

44W LOOX (Nika)

LOOX LINEARLIGHT LED | LED Indoor luminaires



Areas of application

- General illumination
- Home Office
- Commercial spaces
- Meeting rooms
- Corridors

Product benefits

- Energy savings up to 60 % (compared to luminaires that use CFL lamps)
- High luminous efficacy
- Strong structure
- Easy installation with fast connection
- Functional design
- Very homogenous light

Product features

- Type of protection: IP52
- Power factor: PF>0.95
- Warranty : 5 Years




TECHNICAL DATA

Electrical data

Nominal wattage	44.00 W
Nominal voltage	AC110-250V
Mains frequency	50...60 Hz
Power factor λ	0.95

Photometrical data

Luminous flux	4000 lm
Luminous efficacy	90 lm/W
Color temperature	2700K-4000K-6500K
Color rendering index Ra	>80



Dimensions

Dimension	1025*75*52mm
-----------	--------------

Materials & Colors

Product color	White
Housing color	White
Body material	Metal

Application & Mounting

Ambient temperature range	-30...+50 °C
Type of protection	IP52

Dimmable	No
Mounting location	Recessed
Application environment	Indoor

Lifespan

Lifespan	50000 h
Warranty	5 Years

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.