

PRODUCT DATASHEET

HANGING/SURFACE OFFICE

LINEAR LIGHT 30W

Lumination

LOOX LINEARLIGHT LED | LED Indoor luminaires



Areas of application

- General illumination
- Home Office
- Commercial spaces
- Meeting rooms
- Corridors

Product benefits

- Energy savings up to 60 % (compared to luminaires that use CFL lamps)
- High luminous efficacy
- Strong structure
- Easy installation with fast connection
- Functional design
- Very homogenous light

Product features

- Type of protection: IP20
- Power factor: PF>0.5
- Warranty : 2 Years




TECHNICAL DATA

Electrical data

Nominal wattage	30.00 W
Nominal voltage	AC110-240V
Mains frequency	50...60 Hz
Power factor λ	0.5

Photometrical data

Luminous flux	1800 lm
Color temperature	2700K-4000K-6500K
Color rendering index Ra	>80



Dimensions & Weight

Product weight	700g
Dimension	1180*70*43mm

Materials & Colors

Product color	White/Black
Housing color	White/Black
Body material	Polycarbonate

Application & Mounting

Ambient temperature range	-30...+50 °C
Type of protection	IP20

Dimmable	No
Mounting location	Pendant/surface
Application environment	Indoor

Lifespan

Lifespan	25000 h
Warranty	2 Years

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.