

PRODUCT DATASHEET

LINEAR T5 26W OMiLEX

LOOX T5 GLASS TUBE LED | LED Indoor luminaires



Areas of application

- General illumination
- Hotels Office
- Commercial spaces
- Hospitals
- Corridors
- Exhibition halls

Product benefits

- Energy savings up to 60 % (compared to luminaires that use CFL lamps)
- High luminous efficacy
- 180 degrees rotate G13 end cap which can be adjustable in any angle
- Easy installation with fast connection
- Functional design
- Very homogenous light

Product features

- Type of protection: IP20
- Power factor: PF>0.5
- Warranty :1Year
- Beam angle : 120°




TECHNICAL DATA

Electrical data

| | |
|-----------------|------------|
| Nominal wattage | 26 W |
| Nominal voltage | AC165-265V |
| Mains frequency | 50...60 Hz |
| Power factor λ | 0.5 |

Photometrical data

| | |
|--------------------------|-------------|
| Luminous flux | 910 lm |
| Color temperature | 2700K-6500K |
| Color rendering index Ra | >80 |



Dimensions & Weight

| | |
|----------------|-----------|
| Product weight | 205g |
| Dimension | 1177*32MM |

Materials & Colors

| | |
|---------------|-------|
| Product color | White |
| Housing color | White |
| Body material | Glass |

Application & Mounting

| | |
|---------------------------|--------------|
| Ambient temperature range | -30...+50 °C |
| Type of protection | IP20 |

| | |
|-------------------------|--------------------|
| Dimmable | No |
| Mounting location | Fittings, Housings |
| Application environment | Indoor |

Lifespan

| | |
|----------|---------|
| Lifespan | 25000 h |
| Warranty | 1 Year |



DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.