



LUMINATION

# PRODUCT DATASHEET

## Surface Panel 20w Lumination



### Areas of application

- Home
  - Hotels and Catering centers
  - Supermarkets and malls
  - Office and Residential Buildings
- 

### Product benefits

- Energy savings with high system efficacy: up to 70 lm/W
  - High quality aluminum housing
  - Luminaire designed for easy maintenance
  - Professional optics with wide beam angle of 120°
  - Low maintenance and operation costs due to long lifetime of LED
  - Good color consistency
  - Good color rendering
- 

### Product features

- Power factor: > 0.5
- Type of protection: IP20
- Lifetime(L70): up to 25,000 Hrs
- Color rendering index  $R_a$ : > 70




## TECHNICAL DATA

### Electrical data

Nominal wattage	20W
Nominal voltage	185-265V
Power factor $\lambda$	0.5

### Photometrical data

Luminous flux	1300 lm
Luminous efficacy	70 lm/W
Color temperature	2700k-4000k-6500k
Color rendering index Ra	70



### Cut size & Weight

Product weight	S:458 g R:362g
Body size	225*28mm

### Materials & Colors

Product color	White
Body material	PP

### Application & Mounting

Ambient temperature range	-30...+50 °C
Type of protection	IP20

Dimmable	No
Mounting location	Pendant
Application environment	Indoor

### Lifespan

Lifespan	25000 hrs
waranty	2years

---

### DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.