



LUMINATION

PRODUCT DATASHEET

wall light 2*3w+5w Lumination



Areas of application

- Residential
- commercial
- Hotels
- Shop
- Cafe


Product benefits

- Energy savings with high system efficacy: up to 90 lm/W
- High quality aluminum housing
- Luminaire designed for easy maintenance
- Professional optics with wide beam angle of 120°
- Low maintenance and operation costs due to long lifetime of LED
- Good color consistency
- Good color rendering

Product features

- Power factor: > 0.5
- Type of protection: IP65
- Lifetime(L70): up to 30,000 Hrs
- Color rendering index R_a : >70





TECHNICAL DATA

Electrical data

| | |
|-----------------|-----------|
| Nominal wattage | 2*3+5w |
| Nominal voltage | 220-240 V |
| Power factor λ | 0.5 |

Photometrical data

| | |
|--------------------------|---------|
| Luminous flux | 750 |
| Luminous efficacy | 90 lm/W |
| Color temperature | 2700 K |
| Color rendering index Ra | 70 |

Dimensions

| | |
|-----------|--------------|
| Dimension | 200*110*60MM |
|-----------|--------------|

Materials & Colors

| | |
|---------------|----------------|
| Product color | Black |
| Body material | poly carbonate |

Application & Mounting

| | |
|---------------------------|--------------|
| Ambient temperature range | -30...+50 °C |
| Type of protection | IP65 |

| | |
|-------------------------|----------------|
| Dimmable | No |
| Mounting location | Pendant |
| Application environment | Indoor-outdoor |

Lifespan

| | |
|----------|-----------|
| Lifespan | 30000 hrs |
| waranty | 2years |

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.